



ProLux LED Fiber Optic Illuminator

ProLux LED Illuminator sets the standard for the new generation of LED fiber optic illuminators. Harnessing the power of the industry's highest performing high-output LED's, the ProLux LED is as bright or brighter than traditional illuminators, making it a viable alternative to existing halogen technology.

Designed for optimal thermal management to maximize reliability and optical performance, the ProLux LED provides exceptional stability, uniformity and a more consistent color temperature than traditional EKE light sources.

Made in the USA.

Specifications

PROLUX LED FIBER OPTIC ILLUMINATOR	
BRIGHTNESS	Daylight 6000 K
INPUT VOLTAGE	96-264 VAC / 50-60Hz
WORKING TEMPERATURE	0-40 °C
DIMENSION	4.75in x 6in x 9in
LAMP LIFE	Minimum Lifetime of 25,000 Hours
WEIGHT	6.5 lb

Features

- Accepts virtually any light guide with quick change adapters
- Advanced heat pipe technology using metal core PCB's
- Eliminates 100's of lamp replacements
- Exceeds performance of 150w halogen illuminators; higher brightness, better color, longer life, half the energy consumption and reduced ownership costs
- Linear light intensity control with continuous dimming
- Low energy consumption increases safety and reliability
- Maintenance free LED's have a minimum lifetime of 25,000 hours
- Small footprint and rugged housing is suitable for mounting and stacking in space constrained environments
- Superior, precision engineered cooling for extremely quiet operation

Part #	Description	Price
26200A-300	ProLux LED Fiber Optic Illuminator	\$495.00